



DATA SHEET			
Panel	Panel Type	LED-Backlit TFT LCD (TN Technology)	
	Panel Size	23.6"	
	Max. Resolution	FHD 1920 x 1080	
	Pixel Pitch	0.272 mm	
	Brightness	300 cd/m ²	
	Contrast Ratio	20.000.000:1 (DCR)	
	Viewing Angle (H/V)	170°/160°	
	Display Colour	16.7 M	
	Response Time	3 ms	
	Surface Treatment	Anti-Glare Treatment (Haze 25%), 2H Hard Coating	
	Frequency	Frequency (H)	24 kHz -83 kHz
		Frequency (V)	50 Hz - 75 Hz
Signal Input	SDI	BNC x 1	
	DisplayPort	x 1	
	HDMI	1.4 x 1	
	DVI	24-Pin DVI-D	
	VGA	15-Pin D-Sub x 1	
	Composite	BNC x 1	
Signal Output	SDI	BNC x 1	
	Composite	BNC x 1	
External Control	RS232 In	2.5 mm Phone Jack	
Other Connectivity	USB	2.0 x 1 (Service Port)	
Audio	Audio In	Stereo Audio Jack (3.5 mm), Stereo Jack (RCA)	
	Internal Speakers	2W x 2	
Power	Power Requirements	DC 12V, 2.75A	
	On Mode	25W (On)	
	Standby Mode	< 0.5W	
	Off Mode	< 0.5W	
Glass	Thickness	3.0 mm (0.12")	
	Reflection Rate	< 1%	
	Transmission Rate	> 97%	
	Hardness	> 9H	
Operating Conditions	Temperature	0°C - 40°C (32°F - 104°F)	
	Humidity	10% - 90% (non-condensing)	
Mounting	VESA FPM PMI	YES (100 x 100 mm & 75 x 75 mm)	
Stand	Tilt	0° to 18°	
Security	Kensington Security Slot	Yes	
Dimensions	Product with Base (W x H x D)	562.4 x 392.8 x 196 mm (22.1" x 15.4" x 7.7")	
	Product w/o Base (W x H x D)	562.4 x 352.6 x 56.2 mm (22.1" x 13.9" x 2.2")	
	Packaging (W x H x D)	672.0 x 517.0 x 249.0 mm (26.5" x 20.4" x 9.8")	
Weight	Product w/o Base	7.3 kg (16.1 lb)	
	Product with Base	8.1 kg (17.9 lb)	
	Packaging	11.2 kg (24.7 lb)	
Regulation Approval	Certifications & Compliance	CB, CE, FCC, RoHS,, WEEE, REACH	
Accessories	Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	
Optional Accessories	Ceiling Mount (Landscape only)	CMP-01+WMK-03	
	Wall Mount (Landscape only)	WMA-01, WMK-01, WMK-03, PMK-01	
	Desk Mount (Landscape only)	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02	
Power	Power Supply	External	
Storage Conditions	Temperature	-20°C - 60°C (-4°F - 140°F)	
	Humidity	5% - 95% (non-condensing)	