



# MULTILED MX

MULTILED MX	
<b>Luminous Flux</b>	white, 50.000 Lumen
<b>Power</b>	550 W
<b>Supply Voltage</b>	48 Vdc
<b>Bundled PS</b>	Desktop, 48 V, 600 W
<b>Connector</b>	1 x Molex micro-fit 3.0
<b>Heat Dissipation</b>	Active, heatsink and fan
<b>Environmental temp. (operation)</b>	-25°C - 45°C
<b>temp. (Storage)</b>	-25°C - 80°C
<b>Overtemperature Protection</b>	Sensor onboard
<b>IP class</b>	IP 20
<b>Mounting Options</b>	3/8" thread
<b>Standard Lenses</b>	12° x 12° (horizontal x vertical)
<b>Optional Lenses (MX Plus)</b>	25°x 25°, 40° x 40°, 60° x 60°, 30° x 13°, 60° x 12° (horizontal x vertical)
<b>Dimensions</b>	207 * 140 * 88 mm
<b>Weight</b>	1.950 g
<b>Setup</b>	Standalone or G8 controller
<b>Delay / rise and fall time</b>	220ns / 100ns / 350ns
<b>LED</b>	52
<b>Housing</b>	Aluminium
<b>Light modes</b>	Continuous, pulse duration, flank mode with predefined strobe time
<b>Light Intensity</b>	Adjustable, 2%-100%/Off